



INDEX	PROVERJE / modifications	DATE	NAME
-------	--------------------------	------	------

PT approved	ŠTAKLAMA DAT	15.04.15	VIS	KID	TEMP. PUNJEVA	Filling temperature	≤	15 °C	MAZIVNI ŠARŽAJ	Capacity fillant	500 ml ±	ml
	VSI	15.04.15	VIS	HR	ŠARŽAJ CO ₂	CO ₂ content	≤	g/l	TEŽINA	Approx. glass weight	400 g	g
FB released	ŠTAKLAMA DAT		VIS		PROSEDA TERAJNA ŠTICE	Approx. seal thickness	≤	mm	PROSEDA	Approx. seal thickness	3.37 mm	mm
MEASURED	ŠTAKLAMA DAT		VIS		PROVERJE VRAHA	Check connection dia.	≤	mm	PROVERJE	Check connection dia.	27,5 mm	mm
	ŠTAKLAMA DAT		VIS		PROVERJE VRAHA	Check connection dia.	≤	mm	PROVERJE	Check connection dia.	27,5 mm	mm

DIMENSIONS WITH TOLERANCES CONFORM TO STANDARD DIN 6129	METROLOGIC MERE		PRISUK ZRT MERENJA	PROCES	PUNJEVA	MAZIVNI ŠARŽAJ	ŠARŽAJ CO ₂	TEŽINA	PROSEDA	PROVERJE	PROSEDA	PROVERJE
	DIN 6129											

BR. ARTIKLA	6E548.0500.3595	INDEX	A
MAZIV. ARTIKLA	Oliva 400g PP3115 500ml (Muller)	BR. ARTIKLA	6E548.0500.3595
Uspostavljen		BR. ARTIKLA	6E548.0500.3595
Vetropack Straza d.d.		BR. ARTIKLA	6E548.0500.3595
HR-49231 Hum na Silihi		BR. ARTIKLA	6E548.0500.3595
Tel. 00385-49 326 326		BR. ARTIKLA	6E548.0500.3595
www.vetropack.com		BR. ARTIKLA	6E548.0500.3595