


TOLERANCES	
Injection Moulded Dimensions	
0 upto 49 mm	± 0.2 mm
50 upto 99 mm	± 0.3 mm
≥ 100 mm	± 0.5 mm
Blow Moulded Diameter 2.0	
0 upto 14 mm	± 0.3 mm
15 upto 49 mm	± 0.4 mm
50 upto 79 mm	± 0.6 mm
80 upto 149 mm	± 0.8 mm
150 upto 199 mm	± 1.0 mm
≥ 200 mm	± 1.2 mm
Product Height 2.0	
0 upto 74 mm	± 0.6 mm
75 upto 149 mm	± 0.8 mm
150 upto 199 mm	± 1.0 mm
200 upto 249 mm	± 1.4 mm
≥ 250	± 1.8 mm

ART. NO.	SALES TYPE	NOMINAL	FINAL	A3
5020-0100-0034	Standard	100±4.0 ml		
DRAWING NAME	NECK FINISH	BRIMFULL	SCALE (front view) 1:1	
200100S8N	20 SP410 (H12_N)	107±4.0 ml	MATERIAL PET	
DATE	DESIGNER	WEIGHT	All dimensions are in mm This document in design and detail is the property of Berry PET Power and is not to be used or reproduced by unauthorized persons	
18-07-2008	BERRY PET Power	15±1.0 g	TITLE	
20 SP410 100 ml Tall Boston Round				
version: BD&T2021				

ISSUE	DATE	CHANGE / STATUS	APPROVED BY
5.0	17-02-2021	CC5585 / New layout	BM
3.1	31-05-2016	Add Cav. No. location	BM
3.0	25-04-2016	New layout	RvD

müller+krempel   
14.289.20

